



## Quick-Fix Clamp for Cone Flanges

for quick connections of Combiflex PU conical flanges, weld-on conical flanges and conical flanges with spigots, following DIN 3016

### Product Details

#### Construction / Material

- Specification of the connection solution: quick-action clamp for conical flanges based on DIN 3016
- Clamp Design: clamp with turnbuckle, clamping screw in sizes M5-M10 designed as slotted hexagon screw, accidental opening is prevented by a safety pin
- Material of the clamp: stainless steel 1.4301

#### Properties

- Chemical Properties: stainless
- Other: accidental opening is prevented by a safety pin, easy to assemble

#### Operating Temperature

#### Delivery Information

#### Application Areas

#### Customizing Options

### Article Variants

| Article number | DN of the hose<br>mm | Piece weight<br>kg | Minimum free space (D)<br>mm | Free space to open (R)<br>mm |
|----------------|----------------------|--------------------|------------------------------|------------------------------|
| 002183         | 50                   | 0.2                | 147                          | 103                          |
| 002184         | 65                   | 0.26               | 158                          | 103                          |

| Article number | DN of the hose<br>mm | Piece weight<br>kg | Minimum free space (D)<br>mm | Free space to open (R)<br>mm |
|----------------|----------------------|--------------------|------------------------------|------------------------------|
| 002185         | 80                   | 0.29               | 169                          | 103                          |
| 002186         | 100                  | 0.46               | 212                          | 170                          |
| 002187         | 125                  | 0.78               | 241                          | 186                          |
| 002188         | 150                  | 0.86               | 266                          | 202                          |
| 002189         | 160                  | 0.91               | 275                          | 207                          |
| 002190         | 180                  | 0.97               | 289                          | 215                          |
| 002191         | 200                  | 1.05               | 313                          | 228                          |
| 002192         | 250                  | 1.24               | 360                          | 254                          |

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
**+49 209 97077-112**

Product requests via  
[masterflex.de/en](https://masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

