



## Master-VENT 2

Article Master No.: 000456

**Absaug- und Gebläseschlauch aus Co-Polymer beschichtetem Polyestergewebe, sehr leicht, hochflexibel**



hydrolysis  
resistant



microbe  
resistant



compressible



very flexible



light



moderately  
pressure  
resistant

### Product Details

#### Construction / Material

- Type of construction: extruded spiral hose
- Spiral Design: concealed / made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of specified material / coated / double-layered
- Specifications of the wall: flame retardant according to DIN 4102 B2
- Material of the inner layer: aluminium laminate
- Execution of the external layer: coating with co-polymers
- Material of the outer layer: Polyester fabric

#### Properties

- Specifications of the product: complies with DIN EN 13180
- Chemical Properties: good resistance to petrol / good resistance to chemicals / good resistance to oil / good UV resistance / good ozone resistance / hydrolysis resistant / microbe-resistant
- Mechanical Properties: compressible approx. 1:5
- Flexibility: very flexible
- Weight: light
- Pressure Resistance: moderately pressure resistant

- Colour: grey

### Operating Temperature

- Temperature Range: -30 to 140 °C

### Delivery Information

- Delivery, type of production: various nominal widths in standard lengths are available ex-production, individual nominal widths and lengths also ex-stock

### Application Areas

- Areas of application: Ventilation & Air-conditioning / Waste Disposal & Cleaning Technology

### Customizing Options

- optional item modification (on request): other colours / other lengths / other nominal widths / with customer-specific imprint

## Article Variants

| Extended Article Number | Article number | Nominal Size (DN) mm | Bending radius* mm | Weight kg/m | Operating pressure bar | Negative pressure bar | Max. Production length m | Stock Lengths m | Length (standard lengths available for order) m |
|-------------------------|----------------|----------------------|--------------------|-------------|------------------------|-----------------------|--------------------------|-----------------|-------------------------------------------------|
| 000456:51:x             | 000456         | 51                   | 51                 | 0,13        | 0,36                   | 0,4                   | 10.00                    | 10              | 10                                              |
| 000456:63:x             | 000456         | 63                   | 63                 | 0,14        | 0,29                   | 0,29                  | 10.00                    | 10              | 10                                              |
| 000456:76:x             | 000456         | 76                   | 76                 | 0,16        | 0,24                   | 0,22                  | 10.00                    | /               | 10                                              |
| 000456:82:x             | 000456         | 82                   | 82                 | 0,17        | 0,23                   | 0,2                   | 10.00                    | /               | 10                                              |
| 000456:89:x             | 000456         | 89                   | 89                 | 0,18        | 0,21                   | 0,17                  | 10.00                    | /               | 10                                              |
| 000456:102:x            | 000456         | 102                  | 102                | 0,21        | 0,18                   | 0,14                  | 10.00                    | 10              | 10                                              |
| 000456:127:x            | 000456         | 127                  | 127                | 0,25        | 0,14                   | 0,1                   | 10.00                    | 10              | 10                                              |
| 000456:152:x            | 000456         | 152                  | 152                | 0,30        | 0,12                   | 0,08                  | 10.00                    | 10              | 10                                              |
| 000456:160:x            | 000456         | 160                  | 160                | 0,37        | 0,12                   | 0,07                  | 10.00                    | 10              | 10                                              |
| 000456:178:x            | 000456         | 178                  | 178                | 0,39        | 0,11                   | 0,06                  | 10.00                    | /               | 10                                              |
| 000456:203:x            | 000456         | 203                  | 203                | 0,40        | 0,09                   | 0,05                  | 10.00                    | 10              | 10                                              |
| 000456:254:x            | 000456         | 254                  | 254                | 0,58        | 0,07                   | 0,04                  | 10.00                    | 10              | 10                                              |
| 000456:304:x            | 000456         | 304                  | 304                | 0,74        | 0,06                   | 0,03                  | 10.00                    | /               | 10                                              |
| 000456:356:x            | 000456         | 356                  | 356                | 0,90        | 0,05                   | 0,02                  | 10.00                    | /               | 10                                              |
| 000456:406:x            | 000456         | 406                  | 406                | 1,05        | 0,05                   | 0,02                  | 10.00                    | /               | 10                                              |
| 000456:457:x            | 000456         | 457                  | 457                | 1,20        | 0,04                   | 0,02                  | 10.00                    | 10              | 10                                              |
| 000456:508:x            | 000456         | 508                  | 508                | 1,35        | 0,04                   | 0,01                  | 10.00                    | /               | 10                                              |
| 000456:560:x            | 000456         | 560                  | 560                | 1,50        | 0,04                   | 0,01                  | 10.00                    | /               | 10                                              |
| 000456:610:x            | 000456         | 610                  | 610                | 1,60        | 0,03                   | 0,01                  | 10.00                    | /               | 10                                              |

Alle Angaben beziehen sich auf eine Medium- und Umgebungstemperatur von +20°C.

Angabe zum Biegeradius bezogen auf die Innenseite des Schlauchbogens

Technische Änderungen und Farbabweichungen vorbehalten

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

## Suitable for the product



**Hose connector**  
Sheet steel connector for extending, connecting and joining light to medium-weight hoses




**Hose Reducer, symmetrical**  
Hose reducer for extending, connecting and joining light to medium weight hoses



**Hose Clamp with Bolts**  
special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units



**Hose Clamp with Bolts, Steel quality W4, stainless steel 1.4301**  
Special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units



**Master-Grip Hose Clamp, screwable**  
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO



**Master-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301**  
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PVC and Master-SANTO

### Individual consultation

We offer consultation by phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

